

YBF-1E,2E

- Bellows
- Sleeve
- Ball
- Single type
- Double type
- PTEE
- Copper pipe



YBF-1E



YBF-2E

■Features

1. Flexible joint for general piping (to absorb misalignment)
2. Stainless steel wetted parts provide excellent corrosion resistance.

■Specifications


Model	YBF-1E	YBF-2E
Application	Steam, Air, Cold and hot water, Oil, Other non-dangerous fluids	
Maximum pressure	1.0 MPa	15A-200A 1.0 MPa 250A 0.5 MPa
Maximum temperature	220°C	
Material	SS400	
Connection	Stainless steel (SUS 304)	
Braid	Stainless steel (SUS 304)	
Bellows	Stainless steel (SUS 304)	
Connection	JIS Rc screwed (union joint)	JIS 10K FF flanged (loose flanges on both sides)

- Available with tube made of stainless steel (SUS316L).
- Available with all stainless steel made (YBF-6E-7E).
- For vibration absorption around pump, the YBF-2EM (flanged type only) is appropriate. Contact us for details.

■Dimensions (mm)

· YBF-1E


Nominal size	L	Shortest distance between surface
15A		120
20A	300	150
25A	500	150
32A	800	170
40A	1000	180
50A		200



YBF-1E

· YBF-2E

Nominal size	L	Shortest distance between surface	
15A		150	
20A	300		
25A	400		
32A	500		
40A	600		
50A	700		
65A	800		
80A	1000		
100A			
125A	300-400-500		200
150A	600-700-800		
200A	1000-1200		
250A	1500-2000	250	



YBF-2E